

## 15-CD51PTZ

Colour / Monochrome SONY Super HAD Mini Pan / Tilt / Zoom Dome



OPTION	
<b>15-CD08BA</b> Wall Mount Bracket (w/o Dome)	
<b>15-CD03B</b> Ceiling Straight Bracket	

### Feature

- 1/4" SONY Super HAD CCD ICR Camera
- High resolution 480 TV lines, 0.03 Lux (ICR ON)
- 10x optical (3.78-37.8mm) and 10x digital zoom to give a total of 100X Zoom
- OSD on screen display
- AGC, ALC, AES, 48 zone BLC setting, AWB, Preset Mask, or manual control 48 motion detection zones, Image froze
- 360 Degree Rotation, 32 Preset Positions
- Pan Speed Up to 30°/S; Tilt Speed Up To 30°/S
- 6 Auto Cruising Track
- Dimensions: ø 127 mm x 187 mm(H)

**TECHNICAL DATA DOR GUIDANCE PURPOSES ONLY PLEASE VERIFY WITH OUR SALES OFFICE**

<b>SYNC System</b>	Internal Mode / External (AC-Lock) Mode +/- 1Hz
<b>Scanning System</b>	1:2 Interlace
<b>Pick Up Device</b>	1/4" SONY Super HAD CCD
<b>Effective Pixels</b>	NTSC:768(H) x 494(V) / PAL:752(H) x 582(V)
<b>S/N</b>	More than 46dB (r=1, AGC OFF, APC OFF, Y Out )
<b>Horizontal Resolution</b>	480 TV Lines
<b>Lens</b>	F1.6(W)~1.9(T) f=3.7(W)~37.8(T) mm
<b>Zoom</b>	10X Optical Zoom and 10X Digital Zoom
<b>White Balance</b>	ATW / AWB / FIX (Zero Colour Rolling)
<b>ALC</b>	Auto / FIX (OSD Control)
<b>AGC</b>	Auto Gain Control (+24dB Max.)
<b>BLC Function</b>	48 Zone BLC (OSD Control)
<b>ICR Function</b>	Yes
<b>Illumination</b>	0.03 Lux (ICR ON)
<b>Video Signal Output</b>	1.0 Vp-p / 75Ω
<b>GAMMA Correction</b>	0.45 / 1
<b>Electronic Shutter</b>	AES: 1/60(1/50) ~ 1/120,000 sec.
<b>External Control</b>	RS-485
<b>Pan</b>	Speed 0.5~30 °/s
<b>Tilt</b>	Speed 0.5~30 °/s
<b>Preset</b>	32 Preset Positions (Max)
<b>Auto Cruise</b>	6 Auto Cruising Tracks (Max)
<b>Operation Temperature</b>	-30°C~50°C
<b>Operation Humidity</b>	Within 85% RH
<b>Power Source</b>	DC12V +/- 1.0V , 6 W (max)