

COLOR CCD DOME CAMERA



DOME CAMERA


KEY FEATURES

- Ultra compact & light weight
- High sensitivity
- Horizontal resolution 420 TV Lines, 550 TV Lines
- DSP controls for back light compensation, white balance, and gain control
- Built in standard 3.6mm (standard)
- ABS housing

TECHNICAL SPECIFICATIONS

Model	DC-605SH, DC-605SP	DC-606SH, DC-606SP
Image Device	1/3" Sony & Sharp CCD Sensor	
Video Output	Composite 1.0 Vp-p at 75 ohm	
Effective Pixels	NTSC: 512(H) x 492(V) PAL: 512(H) x 582(V)	NTSC: 768(H) x 492(V) PAL: 752(H) x 582(V)
Electronic Shutter	N: 1/60- 1/100,000sec(Auto); P: 1/50-1/100,000sec. (Auto)	
Horizontal	420 TV Lines	550 TV Lines
White balance	Auto white balance (2500°K ~ 9500°K)	
Synchronizing System	Internal	
Sensitivity	0.1 Lux / F2.0 (1/3")	
BLC	Auto	
Signal to Noise	More than 48dB (AGC off)	
AGC	Yes	
Gamma Correction	0.45	
Lens	3.6mm Standard (4mm, 6mm, 8mm Option)	
Power Consumption	120mA ~ 5mA	
Power Supply	12V DC ± 10%	
Temperature	Operating: -10°C to 50°C	
Storage Temperature	-20°C to +60°C	
Construction	ABS	
Dimensions	86(Ø) x 64(H) mm	
Weight	160 g	

MECHANICAL DIMENSION



• Specifications are subjected to change without prior notice.