



Series: KC-7862 30M IR CAMERA

Model: KC-7862 1/3" Color 30M IR & Waterproof

ITEM	DESCRIPTION
Sensor Chip	1/3" SONY CCD/ SONY 11R DSP
Effective pixel	NTSC:510 (H) x492 (V) PAL:500 (H) x582 (V)
Scanning Frequency	NTSC: 15734Hz (H), 60Hz (V) PAL: 15625Hz (H), 50Hz (V)
H. Resolution	420 TV lines
Sensitivity	Color mode automatically switches to B/W mode under 5 Lux 0.1 Lux (IR OFF) ; 0 Lux (IR ON)
Infrared Ray LED	48 pcs
Infrared Ray Distance	Max. 30 Meters
IR Wavelength	850nm
Water Resistant	IP 68
Synchronizing	Internal Sync., 2:1 Interlace
Auto White Balance	AUTO
Auto Gain Control	AUTO
Backlight Compensation	AUTO
S/N Ratio	More than 48dB(AGC OFF)
Gamma Correction	0.45
Electronic Shutter	AUTO 【1/60 (50) ~ 1/100,000】
Video Output	1.0Vp-P75Ω
Lens Mount	6mm Standard Board Lens (4,8,12mm Optional)
Power Requirement	DC 12V/ 490mA
Dimension/Weight	75(Ø)x116(D)mm ; 500g
Operating Temperature	- 10°C ~ +50°C