

KW3266B

DUAL STREAMING H264 MULTIPLEX 16CH CIF REAL-TIME NETWORK DVR(4XHDD)

Support 3G ~ 3.5G Mobile Phone/PDA Streaming
(Symbian/Windows Mobile/iPhone/iPad/Blackberry)

1. H.264 Baseline – 4 recording video quality levels or user defined
2. Multiplex 16CH H.264 DVR: live, recording, playback, backup, network access and control
3. NTSC/PAL software switch and channel Privacy Mask
4. Individual channel schedule recording, multiple channels recording for motion and alarm
5. Support 4 SATA HDD up to 8TB, USB 2.0 Backup with AVI, MPEG4 or H264 Format
6. Audio 16CH In/1CH Out,VGA up to 1920x1080
7. Network capability with Static IP, PPPoE, DHCP, DDNS and E-mail
8. Remote live view, backup, playback, PTZ control and menu setup
9. Dual streaming – individual channel bandwidth setup for limited upload bandwidth
10. Multi-lingual support, Client player(CMS), 3G/3.5G Mobile Players (Symbian/ Windows Mobile/ iPhone/iPad/ Blackberry)

480FPS/400FPS RECORDING



MODEL	KW3266B
VIDEO INPUT/OUTPUT FORMAT	NTSC/PAL: BNC 16CH In/1CH Out, call out
DISPLAY RESOLUTION	NTSC 704 x 480, PAL 704 x 576, real time per channel
COMPRESSION METHOD	Video: H.264 Audio: ADPCM
RECORDING FRAME RATE (FPS) & RESOLUTION	NTSC 120/704 x 480, 240/704 x 240, 480/352 x 240 PAL 100/704 x 576, 200/704 x 288, 400/352 x 288
RECORDING TIME	7~23 days with 500GB HDD for Continuous Recording mode@25fps
RECORDING MODE	Continuous/Schedule/Alarm/Motion Detect, Individual channel schedule recording
HARD DISK CAPACITY	4 x SATA HDD up to 8TB totally, internal DVD Burner capability
MEDIA BACKUP	1 USB 2.0 ports for Flash Disk, DVD Burner, portable HDD backup, AVI, MPEG4, H264 Format
SENSORS, ALARM	16 Inputs, 4 Output(NC, NO relay)
ALARM TYPE	Motion, Sensor, Video loss, Multiple channel recording for Motion and Alarm
AUDIO	16CH In/1CH Out
NETWORK	RJ-45 10/100BaseT Ethernet connector(PPPoE, DHCP, DDNS, Static IP)
VGA OUTPUT	Yes, maximum 1920x1080
PTZ CONTROL	RS-485(RS-422)
I/R REMOTE CONTROLLER	Yes
MOUSE	Yes(OSD operations)
POWER SUPPLY	90~264V AC47-63Hz, 200W Max
OPERATING TEMPERATURE	0°C ~ +45°C
DIMENSION	430(W) x 330(D) x 88(H)mm