

# KW3294B-KW3294C

## DUAL STREAMING H264 MULTIPLEX 4CH CIF REAL-TIME NETWORK DVR(1XHDD)

Support 3G ~ 3.5G Mobile Phone/PDA Streaming  
(Symbian/Windows Mobile/iPhone/iPad/Blackberry)

1. H.264 Baseline – 4 recording video quality levels or user defined
2. Multiplex 4CH H.264 DVR: live, recording, playback, backup, network access and control
3. NTSC/PAL software switch and channel Privacy Mask
4. Individual channel schedule recording, multiple channels recording for motion and alarm
5. Support one SATA HDD up to 2000GB, USB 2.0 Backup with AVI, MPEG4 or H264 Format
6. Audio 4CH In/1CH Out, VGA up to 1920x1080
7. Network capability with Static IP, PPPoE, DHCP, DDNS and E-mail
8. Remote live view, backup, playback, PTZ control and menu setup
9. Dual streaming – individual channel bandwidth setup for limited upload bandwidth
10. Multi-lingual support, Client player(CMS), 3G/3.5G Mobile Players(Symbian/Windows Mobile/iPhone/iPad/Blackberry)

### FRIENDLY OPERATION



KW3294B



KW3294C



MODEL	KW3294B - KW3294C
VIDEO INPUT/OUTPUT FORMAT	NTSC/PAL: BNC 4CH In/1CH Out
DISPLAY RESOLUTION	NTSC 704 x 480, PAL 704 x 576, real time per channel
COMPRESSION METHOD	Video: H.264 Audio: ADPCM
RECORDING FRAME RATE (FPS) & RESOLUTION	NTSC 30/704 x 480, 60/704 x 240, 120/352 x 240 PAL 25/704 x 576, 50/704 x 288, 100/352 x 288
RECORDING TIME	7~23 days with 500GB HDD for Continuous Recording mode@25fps
RECORDING MODE	Continuous/Schedule/Alarm/Motion Detect, Individual channel schedule recording setup
HARD DISK CAPACITY	1 x SATA HDD up to 2000GB
MEDIA BACKUP	1 USB 2.0 ports for Flash Disk, DVD Burner, portable HDD backup, AVI, MPEG4, H264 Format
SENSORS, ALARM	4 Inputs, 1 Output(NC, NO relay)
ALARM TYPE	Motion, Sensor, Video loss, Multiple channel Recording for Motion and Alarm
AUDIO	4CH In/1CH Out
NETWORK	RJ-45 10/100BaseT Ethernet connector(PPPoE, DHCP, DDNS, Static IP)..
VGA OUTPUT	Yes, maximum 1920x1080
PTZ CONTROL	RS-485(RS-422)
I/R REMOTE CONTROLLER	Yes
MOUSE	Optional(OSD operations)
POWER SUPPLY	DC12V/3.5A for AC Adaptor
OPERATING TEMPERATURE	0°C ~ +40°C
DIMENSION	315(W)x224(D)x52(H)mm